

Points 186  Published[Details](#)[Questions](#)☐ Show Question Details

NOTE: Question details not available when more than 25.

 [Acoustics quick glance](#)

STC is a measure for rating the performance of a wall system as a barrier to airborne sound transmission between closed spaces and in many open plan spaces.

 [Acoustics quick glance](#)

The following strategies can be used to comply with HIPAA oral privacy requirements:

 [CH 2](#)

According to ADA, ramp runs shall have a running slope not steeper than 1:12.

 [Ch 1](#)

VOCs can be released from some paint materials into the atmosphere.

⋮ [Ch 1](#)

Thermal transmittance is

⋮ [Ch 1](#)

Indoor Air Quality (IAQ):

⋮ [Ch 1](#)

NFPA denotes UL Class A, B & C Classifications.

⋮ [Ch 2](#)

The main purpose of Means of Egress stairs is to help people safely egress a building during a fire.

⋮ [Ch 2](#)

Regarding a Radiant Heating System:

⋮ [Ch 2](#)

the following flooring materials are ordered in square yards:

⋮ [Chapter 3](#)

STC of 48 – 52 is required between hotel rooms.

⋮ [Chapter 3](#)

Regarding Class (STC) Ratings, higher numbers indicate greater ability to reduce transmitted sound through an assembly.

⋮ [Chapter 3](#)

Regarding fabric wrapped panels, building codes will determine minimum allowable flame & smoke ratings of fabric

⋮ [Chapter 3](#)

ANSI A 137.1 Ceramic Tile classifications based on water absorption rate include:

⋮ [Chapter 4 Ceiling](#)

Acoustical tiles may be perforated or fissured.

⋮ [Chapter 4 Ceiling](#)

Class A/Class 1 fire rating is required for acoustical ceiling tile
used in commercial interiors.

⋮ [Chapter 4 Ceilings](#)

Plenums

⋮ [Chapter 4 Ceilings](#)

Plenum may be filled with

⋮ [Chapter 5 Millwork](#)

Millwork includes

⋮ [Chapter 5 Millwork](#)

Extracting materials from earth is generally not sustainable.

⋮ [Chapter 5 Millwork](#)

Linoleum

⋮ [Chapter 5 Millwork](#)

Marble resists wine stains and would be a good choice for a bar countertop.

⋮ [Formaldehyde](#)

Formaldehyde is considered hazardous by OSHA.

⋮ [Formaldehyde](#)

Formaldehyde

⋮ [IAQ](#)

Indoor levels of air pollutants can be 2-5 times higher, and occasionally 100 times higher, than outdoor levels.

⋮ [IAQ](#)

Indoor air pollution never poses environmental risks to public health.

⋮ [CH 3 walls, partitions, vert comp](#)

Metal frame construction consists of wood partition assemblies using 2x4 or 2x6 nominal dimension lumber.

⋮ [CH 3 walls, partitions, vert comp](#)

Fire treated lumber is chemically coated lumber used for concealed, framed areas where a Class A/Class 1 construction rating is required by code.

⋮ [CH 3 walls, partitions, vert comp](#)

Stone, ceramic tile and concrete surfaces radiate heat at night that was also absorbed during the night.

⋮ [CH 3 walls, partitions, vert comp](#)

Wall assemblies cannot incorporate mechanical, electrical or plumbing systems.

⋮ [Life Cycle Cost Analysis](#)

Life Cycle Cost Analysis Method involves

⋮ [Life Cycle Cost Analysis](#)

Life Cycle Cost Analysis examines long-term costs of a building including

⋮ [Life Cycle Cost Analysis](#)

Life Cycle Cost Analysis may include

⋮ [Life Cycle Cost Analysis](#)

Life Cycle Cost Analysis may consider

⋮ [Love of materials](#)

Some examples of recent innovations in materials and finishes include:

⋮ [OSHA](#)

Personal protective equipment (PPE) may include protective clothing, gloves or respirator.

⋮ [OSHA safety data sheets](#)

Safety Data Sheets include

⋮ [Ch 3 Paint & Wallcovering](#)

Paper wallcoverings are generally very durable and are best suited for high-traffic areas.

⋮ [Specification](#)

A specification

⋮ [Specification](#)

A proprietary specification is one that includes

⋮ [Sherwin Williams 4 products](#)

Designers may specify a microbicidal latex paint, that kills 99.9% of pathogens within 2 hours of exposure on painted surfaces.

⋮ [Sherwin Williams 4 products](#)

Odor Eliminating and Formaldehyde Reducing paint may be used for hospitals.

⋮ [Sherwin Williams 4 products](#)

Two-component waterborne epoxy, formulated to provide excellent corrosion, chemical, abrasion and moisture resistance, may be specified for surgery centers.

⋮ [Teams](#)

Each member brings different skills to the group. The secret to an effective team is discovering how these individual skills work together in the best way possible.

⋮ [Teams](#)

If a shy team member is not contributing, it does not matter. The group does not need to hear from everyone.

⋮ [Teams](#)

By mapping out individual goals on a set timeline, individuals can see how they need to progress as the team project moves along.

 [Specification](#)

One disadvantage to a proprietary specification is that it may limit competition.

 [Specification](#)

A proprietary specification is the most difficult and most time consuming specification to write.

[+ New Question](#)[+ New Question Group](#)[🔍 Find Questions](#)

☐ Notify users this quiz has changed

[Cancel](#)[Save](#)